



TP1059

Weathertightness Test on Quik'n Tuff Cladding Using Rondo Beta-Fix System

Author: Mark Hearfield
Building Physics Technician

Reviewer: John Burgess
Senior Scientist

Contact: BRANZ Limited
Moonshine Road
Judgeford
Private Bag 50908
Porirua City
New Zealand
Tel: +64 4 237 1170
Fax: +64 4 237 1171
www.branz.co.nz



Project Number TP1059	Date of Issue: 12 May 2003	Page 1 of 13 Pages
	Review Date: Indefinite	Copy 1 of 2 Copies

CONDITIONS OF ISSUE OF BRANZ REPORTS

The issue of this Report is subject to the conditions set out below:

Rights

- BRANZ reserves all rights in the Report. The Report is entitled to the full protection given by the New Zealand Copyright Act 1994 to BRANZ. Except as specified below, the client shall not publish any part of a Report.
- The Client will have no rights to use a Report unless full payment of the fees has been made to BRANZ.

Publication of Reports

- The Client shall accurately report any information from BRANZ and shall indemnify BRANZ against any damages related to misrepresentation.
- If the Client has proprietary rights to an Item reported on (e.g. is the manufacturer, accredited agent of the manufacturer, owner), the Client may:
 - a) publish the Report verbatim and in full, or
 - b) state that the Item has been the subject of a Report by BRANZ, provided a full copy of the Report is provided to any third Party requesting it. In New Zealand and Australia such reference to a Report is permitted in technical literature but not in advertising or electronic media, unless the item is BRANZ Appraised.*
- The CEO's prior written consent must be obtained before:
 - a) any extract or abridgement of a Report is published.
 - b) the Report is used in or referred to in connection with any company prospectus or publicly issued report.
- If the Client does not have proprietary rights to an Item, a separate agreement on the use of any contracted report on the Item must be reached prior to commencement of any work by BRANZ.
- BRANZ reserves the right to confirm, to a third party, the validity of any written statement made by the Client which refers to a Report.
- A Report does not imply approval by BRANZ of any Item for any particular purpose and therefore no statement shall state or imply approval by BRANZ.

*In New Zealand and Australia BRANZ allows the use of the following means of referring to a BRANZ Report to support relevant technical claims in Technical Literature:

1. The publishing of a statement that the product has been the subject of a BRANZ Report, provided the statement includes the Report Number, date of issues and date of review.
- or
2. The publishing of words of the Client's choice but only with the approval of BRANZ Chief Executive. Any alterations or amendments, or conditions imposed must be complied with.

(Technical Literature is defined as written material intended to support claims of compliance with a national Building Code and fitness for purpose. It would also be material containing, as a minimum, product specifications, installation instructions, and maintenance requirements.)

WEATHERTIGHTNESS TEST ON QUIK'N TUFF CLADDING USING RONDO BETA-FIX SYSTEM

1. CLIENT

EIFS International
PO Box 2106
Wellington
New Zealand

2. SAMPLE DESCRIPTION

The system as tested was a 'Quik'n Tuff' wall system consisting of Conpolcrete™ cladding panels installed on a timber frame using 'Rondo Beta-Fix System' metal channel and clip battens. Clear plastic was used instead of the reflective sarking and was mounted between the cladding and framing (Figure 1). The bottom plate detail used was Rebated Slab Type 1 (AS/NZ) (Figure 2).

The panel was constructed with one recessed window and one face fixed window. A 200mm kickback in the timber frame was used to give an external (male) and internal (female) corner in the sample. The internal corner also contained a vertical control joint (see Photo 1).

The sample was built by the client. Cladding fixing and corner details were in accordance with the manufacturers specifications as detailed in Figures 1-12.

Masking tape was used as the air-seal at the internal face of the windows. Internal linings were replicated by holding air pressure at the line of the building wrap.





Photo 1 Sample layout

MEH 292

JCB



REF No.	QTES-001
REV.	B
DATE.	15/04/03
DETAIL No.	7.1 3.7

QT ECO SERIES

QT Wall PANEL

Figure 1: System Overview

MEH 252

JCB

NOTE 2

WEATHERSEALING SEALANT FOR EXTERIOR WALL CONSTRUCTION AND AS A GENERAL PURPOSE GAP-FILLING SEALANT FOR EXTERIOR USE (BRANZ APPRAISAL No. 311 OR 419 OR 435 APPLIED TO MANUFACTURER'S RECOMMENDATIONS)

STEEL OR TIMBER * STUD FRAMING

INTERNAL WALL LINING *

RONDO BETA-FIX CLIP * AND CHANNEL

SELECTED SKIRTING BOARDS *

30 NOMINAL QT PANEL


- REFLECTIVE SARKING BUILDING PAPER WIND BARRIER TO NZ3604
- 80 x 80mm PLATED SCREWS (CLASS 3) WITH QT_W BUTTONS AT 300 CENTRES (VERTICAL)

- QT_W REINFORCING MESH
- CONPOLCRETE™
- PROPRIETARY COATING SYSTEM

- QT_W DAMP PROOF MEMBRANE (SLAB) 150 DPM FIXED TO STUDS WITH GALVANISED NAILS OR SCREWS

- QT_W WEERHOLES AT PANEL JOINTS

MAXIMUM PAVED LEVEL 1:20 MINIMUM FALL AWAY FROM BUILDING *



SCALE: A4=1:2

PANEL TO SLAB REBATE 15mm TOLERANCE FOR TIMBER SHRINKAGE


- PROPRIETARY EXTERIOR WEATHERPROOF SEALANT WITH BACKING ROD (SEE NOTE 2)

SLAB-ON-GROUND REBATED SLAB TYPE 1 (AS/NZ) USING RONDO BETA-FIX SYSTEM

SCALE: A4=1:5

REF No.	QTES-001
REV.	B
DATE	18/04/03
DETAIL No.	7.2.10

Figure 2 Footing detail



VERTICAL EXPANSION JOINT TYPE 1 (AS/NZ) USING RONDO BETA-FIX SYSTEM

SCALE: A4=1:5

REF No.	QTES-001
REV.	A
DATE	21/04/03
DETAIL No.	7.8.8


Figure 3: Vertical Control Joint

MEH 2 22

JCB

JCB






QTmECO SERIES PANEL
TYPICAL EXTERNAL CORNER DETAIL (AS/NZ)
USING RONDO BETA-FIX SYSTEM

SCALE A4=1:2

REF No.	QTES-001
REV	B
DATE	18/04/03
DETAIL No.	7.1.6.10

Figure 4: External Corner



QTmECO SERIES PANEL
TYPICAL INTERNAL CORNER DETAIL (AS/NZ)
USING RONDO BETA-FIX SYSTEM

SCALE A4=1:2


REF No.	QTES-001
REV	B
DATE	18/04/03
DETAIL No.	7.1.6.8

Figure 5: Internal Corner

MEH 242



JCB



QT_{MECO} SERIES PANEL
 USING RONDO BETA-FIX SYSTEM
 TYPICAL CONSTRUCTION DETAIL

SCALE: A4=1:5

REF No	QTES-001
REV	B
DATE	18/02/03
DETAIL No.	7.1.6.6

Figure 6: Cladding Cross Section

MEH *252*

JCB







Figure 7: Flush Window Jamb Details

Quick'nTuff Wall Systems

Flush Window - Sill Detail (NZ)

-  Building Wrap
-  Damp Proof Membrane
-  Weatherproof Sealant




Figure 8: Flush Window Sill Details

MEH 242

JCB
JCB




Figure 9: Flush Window Head Detail




Figure 10 Recessed Window Jamb Detail

MEH 242

JCB







Figure 11 Recessed Window Head Detail

-  Building Wrap
-  Damp Proof Membrane
-  Weatherproof Sealant




Figure 12 Recessed Window Sill Detail

MEH *2/2/03*

JCB

3. TEST

The sample was installed in the BRANZ weathertightness testing facility on Monday 5 May 2003 followed by testing to the general procedure of AS/NZS4284. The client was present.

The test was undertaken to determine the compliance of the composite cladding system and joints with the requirements of clause E2 of the New Zealand Building Code, through the use of an extension to the verification method included in clause E2 of the New Zealand Building Code – E2-VM1. BRANZ has established that for monolithic cladding systems assurance of weathertight performance is achieved through the modified use of the AS/NZS4284 building façade weathertightness test followed by a BRANZ-designed extension to this test, as outlined below.

3.1 Standard AS/NZS4284:1999 test

The standard test requirement is E2-VM1. This involves the exposure of a test sample to the requisites of clause 7.5 and 7.6 of the AS/NZS4284 'Testing of Building Facades'. Clause 7.5 involves subjecting the sample to a minimum of a 5 minute pre-wetting, followed by static air pressure at 300Pa and concurrent water spray exposure for 15 minutes at a minimum rate of 0.05 l/m²s. Clause 7.6 involves subjecting the sample to fluctuating air pressure with concurrent water spray at the same intensity. The first stage of this exposure is at a pressure that fluctuates between 150 Pa and 300Pa. The second stage has a fluctuating air pressure varying between 300 and 600 Pa, and the third stage involves varying the air pressure application from 0.3 Wp to 0.6 Wp, where Wp is the design pressure of the site, or in the absence of a specification is 2kPa. Stages two and three are not typically performed for domestic buildings.

Note: Given that the requirements for testing and the pass/fail criteria are currently under discussion by the BIA, the following are BRANZ current interpretations of the requirements for appraisal purposes. It is required that the external cladding prevent the passage of water through it during the static pressure portion of the standard test. The cyclic pressure test is not routinely performed. If the sample initially fails, documented modifications are able to be made (such as the application of sealant) to prevent the entry of water. These modifications must be assessed, and practical solutions to the leakage found before a 'pass' will be registered in this test.

MEH 2 42

JCB

3.2 Modified AS/NZS4284:1999 test

Firstly, the static pressure regime of the standard test is applied across the wet wall only, rather than across the complete sample. This is achieved through either modifying the area of vents between the batten cavity and the test conditions, or by modifying the leakage area through the clear plastic, simulating the housewrap and the internal drywall. This test replicates the effect of the cyclic pressure from the AS/NZS4284 test, in a known way.

Secondly, defects are introduced through the external face of the cladding system to assess the ability of the secondary defences of the cladding system to remove water without wetting the framing cavity or framing. A static pressure is then generated across the wetwall only. The defects typically take the form of five mm diameter holes (or equivalent) that are formed through the external cladding to allow water to penetrate to the secondary line of defence, which may be formed of the building paper/building wrap, flashings and sealing materials. These were located in the following places, and introduce water through to the outer face of the building paper:

- I. Through the LH jamb of a window (See Photo 2)
- II. Through the RH jamb of a window (See Photo 2)
- III. Through the cladding immediately above the window head (See Photo 2)
- IV. Through the vertical control joint (See Photo 2)




Photo 2: Introduced defects

Note: In the modified test, it is required that the cladding system manage any penetrating water, and demonstrate no transference of water from the back of the cladding or any cavity structure onto the face/line of the building wrap (plastic). Documented modifications are able to be made during the test to result in a pass. Spattering of water directly onto the building wrap (plastic) from defects is not deemed a fail.

Each instance where water was not controlled by the secondary defences but was able to wet the building wrap over the insulation cavity or framing and travel more than 300mm is labelled a fail. A pass is achieved where the system adequately controls water that has entered the cladding cavity without wetting the building wrap over the insulation cavity or the framework as viewed from the line of the interior lining.

MEH

25/11

JCB

4. RESULTS

4.1 Results of Test to method from AS/NZS4284:1999 test (E2-VM1)

Pass

4.2 Results of Modified AS/NZS4284:1999 test

Pass.

4.3 Discussion

- Initial testing showed a defect in the footer which resulted in spattering of water within the cavity up 1200mm. This was modified to an 'L shape' to seal the cavity flashing as was intended.
- The recessed window initially had a leak through the left hand sill weep hole when tested at static pressure, which resulted in water hitting the wrap with water at 1 drop per second flowing down the back of the cladding panel. Then at both the cyclic and the static pressure tests the leakage increased to 10 drops/second from the weep hole flowing down the back of the cladding, but not hitting the wrap. The weep hole was sealed and further testing was successful.
- The testing showed that 90% of the air pressure difference was across the cladding panel. with only 10% falling across the housewrap.

MEH

2/22

JCB